OLYMPUS®

C-750 ULTRA ZOOM Unparalleled power and control. Remarkable ease.

Powerful 40x Total Zoom An incredible **10x optical zoom** with **ED elements** gives you photos filled with sharp detail and vibrant color. And a **4x digital zoom** combines for a **40x total seamless zoom** equivalent to a staggering 1520mm in 35mm photography.

4.0 Megapixel CCD (Effective) Perfectly cropped prints 8" x 10" and larger. Small images easy to e-mail. And every picture in between.

TruePic™ Uses every pixel for every image, so even pictures shot at lower resolution settings are sharp and clear.

Total Control **Full auto mode. Manual mode. Aperture and shutter priority modes. Six Scene Programs. Four customizable My Modes.** Take your pick, then take the shot.

Endless Flexibility **QuickTime® movies with sound. TTL hot shoe. Intuitive menu system** and more. All in a **compact**, **powerful** camera.

Auto-Connect USB Connects to nearly any USB computer **automatically**, including **Windows® XP** and **Mac® OS X** systems.

Olympus Innovation It's the feature most responsible for the most realistic digital images you can get. **Nothing's impossible.**

CAMEDIA®

CAMEDIA C-750 ULTRA ZOOM   Stock No. 225390

Package Contents	CAMEDIA C-750 Ultra Zoom Digital Camera, 16MB xD-Picture Card™, (4) AA NiMH Batteries and Charger, Digital Camera Win/Mac USB Cable, Audio/Video Cable, Neck Strap, Lens Cap/Retainer Cord, Quick Start Guide, Printed Instruction Manual, Warranty Card, CD-ROM: CAMEDIA Master Software, Adobe Acrobat® Reader, Windows 98 Rev 2 Driver, Camera Reference Manual
System Requirements (for camera Auto-Connect USB)	Supported on USB-equipped Windows 2000 Pro, ME and XP computers. Windows 98 Rev 2 requires provided driver* to be loaded for support. Macintosh requirements include Power Macintosh with built-in USB port and OS 8.6 – OS X or higher. Mac OS 8.6 requires mass storage driver 1.3.5 available at apple.com. Downloading to laptop computer without USB port possible with optional PCMCIA xD-Picture Card™ reader.
System Requirements (for included CAMEDIA Master software)	Windows® IBM PC/AT, Pentium or greater, Windows 98 second edition/ ME/2000 Pro, CD-ROM compatible drive, 64 MB RAM or greater, 120 MB minimum available HD space, USB port, Monitor with thousands of colors (millions of colors recommended). Macintosh® USB iMac, G3, G4 or greater, OS 8.6 – OS X or higher, CD-ROM drive, 64 MB RAM or greater, 120 MB minimum available HD space, USB port, Monitor with thousands of colors (millions of colors recommended). Check the Olympus website for updated information on system requirements for software and support. *Software driver supplied on enclosed CD

Memory Card Storage Capacity

Quality	Pixel Resolution	16MB xD-Picture Card (included)	256MB xD-Picture Card
OIE: SHQ, HQ	3200 x 2400*	2, 8 shots	45, 136 shots
3:2 TIFF, SHQ, HQ	2304 x 1536	1, 6, 18 shots	25, 100, 290 shots
TIFF	2304 x 1728 to 640 x 480	1 to 16 shots	22 to 270 shots
SHQ, HQ	2304 x 1728	5, 16 shots	89, 261 shots
SQ1 (High, Normal)	2048 x 1536, 1280 x 960	8 – 49 shots	140 – 799 shots
SQ2 (High, Normal)	1024 x 768, 640 x 480	26 – 165 shots	431 – 2663 shots
HQ	320 x 240 15 fps movie	33 sec. per sound movie	33 sec. per sound movie
SQ	160 x 120 15 fps movie	148 sec. per sound movie	148 sec. per sound movie

All still image capacity figures are approximated without audio. *Optimum Image Enlargement resolution is interpolated from maximum optical resolution of 2288 x 1712.

Ultra-powerful zoom lens. Advanced photographic options.

Visit our website to see everything else we

packed into this stylish, compact, amazing digital camera.

olympusamerica.com/c-750

OLYMPUS®